

FROM 6,0 KW TO 22 KW.

CHA/IK/A 21÷81

A CLASS ENERGY EFFICIENCY AIRCOOLED LIQUID CHILLERS AND HEAT PUMPS WITH AXIAL FANS, INVERTER SCROLL COMPRESSOR, PLATE EXCHANGER AND HIGH EFFICIENCY EC INVERTER CIRCULATOR.



The CHA/IK/A 21÷81 **COMPACT LINE** series is the winning choice for ideal comfort in residential and commercial environments. The range, in A CLASS energy efficiency, features Inverter technology on the compressor, for a high efficiency at partial loads. The range excels for its compact sizes, quietness and optimised water circuit, on a peraluman structure. Particular design features enable immediate and effective use, easy installation and lasting reliability. These extremely compact and high-tech units offer you ideal comfort in all seasons.

The unit features high efficiency integrated circulator with EC Inverter brushless electronic motor. The Heat Pump version is designed for **hot water production up to 55 °C**.

The units are compliant to the ErP Regulation.

COMPACT Line

INVERTER SCROLL

VERSION

CHA/IK/A

CHA/IK/A/WP

Cooling only

Reversible Heat Pump

FEATURES

- Structure with supporting frame, in peraluman, galvanized sheet and with rubber shock absorbers on the frame.
- DC INVERTER Scroll compressor with internal overheat protection and crankcase heater.
- Axial fans with low ventilation and special wing profile, directly coupled to external rotor motors.
- Condenser made of copper tubes and aluminium finned coil, complete with drain pan for WP version only.
- Evaporator AISI 316 stainless steel braze welded plates type, complete with water differential pressure switch. On the Heat Pump units it is always installed an antifreeze heater.
- Electronic expansion valve.
- R410A refrigerant.
- Electrical board includes: main switch with door lock device, fuses, compressor and pump remote control switch.
- Condensing Control is included: electronic proportional device that ensures efficient and continuous functioning of the unit with outside air temperature down to -20 °C in cooling mode. It also allows to reduce the sound level especially at night. It consists of a fans speed controller with continuous speed regulation and high and low pressure transducers on cooling circuit.
- Functioning in heating mode with outside air temperature down to -15 °C.
- Water circuit includes: water differential pressure switch, high efficiency EC Inverter circulator, safety valve and expansion vessel.
- High efficiency circulator with EC Inverter brushless electronic motor with 3 speeds selectable by the user.
- Microprocessor control and regulation system.

ACCESSORIES

FACTORY FITTED ACCESSORIES

- TX Coil with pre-coated fins
- FE Antifreeze heater for evaporator

LOOSE ACCESSORIES


- CR Remote control panel
- IS Modbus RTU protocol, RS485 serial interface
- RP Coil protection metallic guards

MODEL			21	31	41	51	61	71	81
Cooling	Cooling capacity (1)	kW	6.0	7.6	9.3	12.4	15.7	19.0	22.4
	Absorbed power (1)	kW	1.8	2.4	3.0	3.8	4.9	6.0	7.2
	EER (1)		3.33	3.17	3.10	3.26	3.20	3.17	3.11
Cooling (EN14511)	Cooling capacity (1)	kW	6.0	7.6	9.3	12.4	15.6	18.9	22.5
	Absorbed power (1)	kW	1.8	2.4	3.0	3.8	4.9	6.0	7.2
	EER (1)		3.33	3.17	3.10	3.26	3.18	3.15	3.13
	SEER (2)		4.12	4.11	4.10	4.68	4.74	4.71	4.72
	Energy Efficiency (2)	%	162	161	161	184	187	185	186
Heating	Heating capacity (3)	kW	6.7	8.8	10.9	14.1	17.5	20.9	24.8
	Absorbed power (3)	kW	1.9	2.5	3.2	4.0	4.9	5.9	7.0
	COP (3)		3.53	3.52	3.41	3.53	3.57	3.54	3.54
Heating (EN14511)	Heating capacity (3)	kW	6.7	8.8	10.9	14.1	17.5	20.9	24.8
	Absorbed power (3)	kW	1.9	2.5	3.2	4.0	4.9	5.9	7.0
	COP (3)		3.53	3.52	3.41	3.53	3.57	3.54	3.54
	SCOP (4)		3.49	3.34	3.45	3.42	3.56	3.60	3.85
	Energy Efficiency (4)	%	136	131	135	134	139	141	151
	Energy Class (5)		A+	A+	A+	A+	A+	A+	A++
Compressor	Quantity	n°	1	1	1	1	1	1	1
Electrical characteristics	Power supply	V/Ph/Hz	230/1/50			400/3+N/50			
	Max. running current	A	16	16	16	13	13	15	18
	Max. starting current	A	10	10	10	8	8	9	10
Water circuit	Water flow	l/s	0.29	0.36	0.44	0.59	0.75	0.91	1.07
	Pump available static pressure	kPa	53	56	52	76	82	70	60
	Water connections	"G	1"	1"	1"	1"	1"	1"	1"
Sound pressure (6)		dB(A)	51	52	55	57	58	59	60
Weights	Transport weight	Kg	101	113	123	195	197	199	201
	Operating weight	Kg	126	138	148	245	247	249	251

DIMENSIONS			21	31	41	51	61	71	81
L	STD	mm	870	870	870	1160	1160	1160	1160
W	STD	mm	320	320	320	500	500	500	500
H	STD	mm	1100	1100	1100	1270	1270	1270	1270

CLEARANCE AREA

CHA/IK/A 21÷41



CHA/IK/A 51÷81



NOTES

- Chilled water from 12 to 7 °C, ambient air temperature 35 °C.
 - Seasonal energy efficiency of cooling at low temperature. According to EU Regulation n. 2016/2281.
 - Heated water from 40 to 45 °C, ambient air temperature 7 °C d.b./6 °C w.b.
 - Seasonal energy efficiency of heating at low temperature with average climatic conditions. According to EU Regulation n. 813/2013.
 - Seasonal energy efficiency class of heating at low temperature with average climatic conditions. According to EU Regulation n. 811/2013.
 - Sound pressure level measured in free field conditions at 1 m from the unit. According to ISO 3744.
- N.B. Weights of WVP version are specified on technical brochure.